



$$\begin{aligned} \text{Rating of Coupling} &= \frac{\text{KW}}{\text{RPM}} \times 100 = \frac{9.32 \times 1}{(\text{SF}) \times 100} \times 100 = 1440 \\ &= 0.65 \text{ KW} / 100\text{RPM} \\ \text{Recommended Coupling Size} &= \text{TRF} - 60 \end{aligned}$$

SIZE	Power Per 100 rev / min	Max Speed Rev / min.	Bore		A MM	L MM	D MM	E MM	C MM	G MM	M+ MM	F MM	Apprax
			Min MM	Max MM									Wts. (Kgs.)
TRF - 40	0.22	4500	13	30	104	66	-	22	82	43	22	-	1.6
TRF - 50	0.56	4500	18	38	133	89	79	32	100	43	25	-	2.4
TRF - 60	1.11	4000	18	48	165	109	73	38	125	43	33	-	4
TRF - 70	1.7	3600	20	55	197	130	82	45	144	10	40	101	6.2
TRF - 80	2.65	3100	26	65	211	145	95	51	167	10	43	106	9.6
TRF - 85	3.2	3000	32	70	222	150	103	53	179	13	44	107	11.5
TRF - 90	3.82	2880	32	76	235	160	110	57	188	13	46	119	14
TRF - 100	5.29	2600	32	85	254	168	124	60	216	13	48	123	20
TRF- 110	7.46	2300	32	90	279	174	134	65	133	14	44	127	26
TRF - 120	12.4	2050	39	102	314	201	152	76	264	14	49	140	32
TRF - 140	19.4	1800	75	120	359	211	195	89	311	14	24	152	54
TRF - 160	32.6	1600	75	140	402	134	216	102	345	19	30	156	82
TRF - 180	57.4	1500	75	175	470	274	266	114	398	19	46	188	126